

GENERATOR SOLUTIONS

STORM SERIES

YNS38K SPECIFICATIONS 38kVA



Australian Design.
Powered by



GENERAL

Model	K
Power Type	Diesel
Prime Power (kW/kVA)	28/35
Standby Power (kW/kVA)	30.8/38.5

ENGINE

Engine Make and Model	KUBOTA V3300T-E2BG
Engine Type	Water-cooled, Inline, 4 stroke
Fuel Consumption (L/h)*	7.5
Aspiration	Natural
Bore (mm) x Stroke (mm)	98 x 110
No. of Cylinders	4
Displacement (L)	3.318
Compression Ratio	21.8
Governor Type	Mechanical governor
Lubricating Oil Capacity (L)	13.2

*Fuel Consumption is based on 100% load

ALTERNATOR

Model	SLG184H1
Frequency (Hz)	50
Rate Power (kW/kVA)	30/37.5
Power Factor	0.8
Exciter Type	Self-excited
Voltage Regulator	AVR
Voltage Regulation	+1.0%
No. of Phases	3
Insulation	Class H
Protection	IP 22
Altitude (m)	1000

UNIT

Dimensions L x W x H (m)	2.3 x 1.0 x 1.5
Dry Weight (kg)	1460
Sound at 7m/dB	70

STANDARD FEATURES

- 50°C rated radiator
- Powder coated finish
- All moving parts fitted with safety guards
- Emergency E stop
- State of the art control system
- Outlets 2 x 3PH 32amp
- Outlets 2 x 1PH 15amp
- ATS available
- Single phase units available



ASSEMBLY

The engine and alternator are closed coupled by means of an SAE flange. A full torsional analysis has been carried out to guarantee no harmful vibration will occur. Anti-vibration pads are affixed between engine alternator feet and base frame. Rubber diagonal isolators are specifically designed to reduce engine and alternator vibration and prevent distortion in the voltage and harmonic output of the generator. All iron and steel surfaces of the canopy fabrication have been sand blasted and then powder coated, which provides an excellent corrosion resistant surface.



CONTROL SYSTEM

Automatic stop/start, Data measurement, Alarm protection and remote control, remote measuring and remote communication; SG485 module must be fitted in. LCD display and it is easy and reliable to use.



QUALITY STANDARDS

Our generator sets are compliant with all the main standards, such as ISO8528, ISO14000, GB755, BS5000, VDE0530, ISO3046, IEC34-1, AS3000.

WARRANTY POLICY

12 months, 1200 hours as per generator.
Generators Australia Pty Ltd Warranty Policy.
All photos are for marketing purposes only.