

YNS700V SPECIFICATIONS 700kVA



Australian Design.
Powered by



GENERAL

Model	YNS700V
Power Type	Diesel
Prime Power (kW/kVA)	500/625
Standby Power (kW/kVA)	560/700

ENGINE

Engine Make and Model	VOLVO TWD1643GE
Engine Type	Turbo-charged, Low temp after-cooled, In-line, 6cyl
Fuel Consumption (L/h)*	125.5
Aspiration	Turbo-charged, Air-to-air charge cooled
Bore (mm) x Stroke (mm)	144 x 165
No. of Cylinders	6
Displacement (L)	16.12
Compression Ratio	16.5:1
Governor Type	EMS2
Lubricating Oil Capacity (L)	48

*Fuel Consumption is based on 100% load

ALTERNATOR

Model	SLG354F1
Frequency (Hz)	50
Rate Power (kW/kVA)	536/670
Power Factor	0.8
Exciter Type	Self-excited
Voltage Regulator	AVR
Voltage Regulation	+0.5%
No. of Phases	3
Insulation	Class H
Protection	IP 21
Altitude (m)	1000

UNIT


Dimensions L x W x H (m)	5.1 x 2.1 x 2.43
Dry Weight (kg)	5600
Sound at 7m/dB	83

STANDARD FEATURES

- 50°C rated radiator
- Powder coated finish
- All moving parts fitted with safety guards
- Emergency E stop
- State of the art control system
- ATS available

ASSEMBLY

The engine and alternator are closed coupled by means of an SAE flange. A full torsional analysis has been carried out to guarantee no harmful vibration will occur. Anti-vibration pads are affixed between engine alternator feet and base frame. Rubber diagonal isolators are specifically designed to reduce engine and alternator vibration and prevent distortion in the voltage and harmonic output of the generator. All iron and steel surfaces of the canopy fabrication have been sand blasted and then powder coated, which provides an excellent corrosion resistant surface.



CONTROL SYSTEM

Automatic stop/start, Data measurement, Alarm protection and remote control, remote measuring and remote communication; SG485 module must be fitted in. LCD display and it is easy and reliable to use.



QUALITY STANDARDS

Our generator sets are compliant with all the main standards, such as ISO8528, ISO14000, GB755, BS5000, VDE0530, ISO3046, IEC34-1, AS3000.

WARRANTY POLICY

12 months, 1200 hours as per generator. Generators Australia Pty Ltd Warranty Policy. All photos are for marketing purposes only.