GENERATOR SOLUTIONS

STORM SERIES

YNS825C SPECIFICATIONS 825kVA





GENERAL

 Model
 YNS825C

 Power Type
 Diesel

 Prime Power (kW/kVA)
 600/750

 Standby Power (kW/kVA)
 660/825

ENGINE

Engine Make and Model

Engine Type

Fuel Consumption (L/h)*

Aspiration

Bore (mm) x Stroke (mm)

No. of Cylinders Displacement (L)

Compression Ratio

Governor Type

Lubricating Oil Capacity (L)

*Fuel Consumption is based on 100% load

CUMMINS KTA38-G2

Turbocharged, Aftercooled, In-line, 12Cyl

167

Turbo-charged, Aftercooled

159 x 159

12

38

14.5:1

Electronic governor

135.1

ALTERNATOR

SLG404G11 Frequency (Hz) Rate Power (kW/kVA) 648/810 Power Factor 8.0 **Exciter Type** PMG Voltage Regulator AVR ±0.5% Voltage Regulation No. of Phases Insulation Class H Protection IP 21 Altitude (m) 1000

UNIT

Dimensions L x W x H (m) 5.8 x 2.25 x 2.58

 Dry Weight (kg)
 8400

 Sound at 7m/dB
 90

STANDARD FEATURES

- 50°C rated radiator
- Powder coated finish
- All moving parts fitted with safety guards
- Emergency E stop
- State of the art control system
- ATS available

ASSEMBLY

The engine and alternator are closed coupled by means of an SAE flange. A full torsional analysis has been carried out to guarantee no harmful vibration will occur. Anti-vibration pads are affixed between engine alternator feet and base frame. Rubber diagonal



isolators are specifically designed to reduce engine and alternator vibration and prevent distortion in the voltage and harmonic output of the generator. All iron and steel surfaces of the canopy fabrication have been sand blasted and then powder coated, which provides an excellent corrosion resistant surface.

CONTROL SYSTEM

Automatic stop/start,
Data measurement, Alarm
protection and remote control,
remote measuring and remote
communication; SG485
module must be fitted in. LCD
display and it is easy and reliable to use.



QUALITY STANDARDS

Our generator sets are compliant with all the main standards, such as ISO8528, ISO14000, GB755, BS5000, VDE0530, ISO3046, IEC34-1, AS3000.

WARRANTY POLICY

12 months, 1200 hours as per generator. Generators Australia Pty Ltd Warranty Policy. All photos are for marketing purposes only.